

HD3



Hotel/hospitality
features



DECT handset



Customisable
faceplate



Anti-bacterial
housing



HD audio

Additional cordless DECT handset for HD351W/HD351A with charging cradle

With the HD3 you can expand your HD351W and HD351A with up to 4 or 3 additional cordless handsets and thus offer your guests all the advantages in a larger space, as you can make calls in up to 5 locations/rooms. In addition to their own charging cradle, all handsets have the most important features for the comfort of your guest:

hands-free calling, muting and call hold are integrated, individual key functions can be stored! The HD3 has an antibacterial housing to protect against germs and is easy to clean. A large visual display alerts the guest to calls or waiting messages. The handsets can be individually labeled.

Basics and equipment

- Product information
 - Cordless DECT handset | Charging cradle | PN 00007011
 - Colour: gunmetal black
 - Sturdy, solid construction
 - [Customisable section for colour or hotel branding¹](#)
 - Anti-bacterial housing
- Placement: indoor, desktop, nightstand

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - DECT handset: 48 mm × 21 mm × 203 mm
 - Charging cradle: 51 mm × 121 mm × 133 mm
 - DECT handset (on the charging cradle, desk mounted): 53 mm × 56 mm × 216 mm
- Weight (approx.)
 - DECT handset: 145 g
 - Charging cradle: 72 g
 - DECT handset (on the charging cradle, desk mounted): 344 g

Indicators and keys

- DECT handset: 5 LED indicators
 - Message waiting indication (MWI): 1 red LED
 - Flash/Talk key indication: 1 green LED
 - Speakerphone mode: 1 red LED
 - Mute status indication: 1 red LED
 - Low battery indication: 1 red LED
- Charging cradle: 1 LED indicator
 - Charging indication: 1 red LED
- DECT handset: 23 hard keys in total
 - 12 keys (standard ITU telephone keypad), backlit
 - 4 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with red LED)
 - Volume +
 - Volume -

- 3 programmable function keys
 - Speed dialling
- 4 dedicated function keys:
 - Offhook (with green LED)
 - Onhook
 - Message
 - Hold

Audio devices and features

- Microphone
- Handset earpiece
 - Hearing aid compatible (HAC)
- External speaker
 - Speakerphone mode
- Built-in assignable ringtones

Interfaces and connections

- Power options
 - DECT handset: Battery lithium-ion, 3.7 V, 1,000 mAh, removable, rechargeable, up to 7 h talk time, up to 120 h standby time, up to 11 h charging time
 - Charging cradle: Power adapter (VT-PLII) 100 - 240 V AC, 50/60 Hz, 150 mA | 6 V DC, 450 mA, 2.7 W
- Wired interfaces
 - Charging cradle: coaxial power connector (socket)
- Wireless interfaces
 - DECT³

DECT technology and features

- Standard: DECT³
 - Wideband audio
- Frequency band
 - EU & UK & AU: 1,881.792 - 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode (via dedicated function key)
- Hold (via dedicated function key)
- [Multicast paging](#)

Environmental conditions

- Operating ambient temperature:
 - 5 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Package contents

- Hardware
 - DECT handset HD3
 - Battery
 - Charging cradle
 - Power adapter
- Documentation
 - [Quick Installation Guide](#)

Snom accessories and compatible devices

- Guest room phone:
 - [HD351W \(PN 00007009\)](#)
 - [HD351A \(PN 00007031\)](#)
- Battery HD3 (PN 00004627)
- Power adapter: HD3 PSU
 - EU: PN 00004683
 - UK: PN 00004684
 - AU: PN 00004685

Series overview



HM201



HM2



HD100



HD101



HD1



HD300²



HD30L²



HD350W²



HD351W²



HD3

¹ Available separately

² Also available as analogue model

³ DECT devices manufactured for the USA and Canada are marketed as DECT 6.0

Disclaimer

Further information: [Snom HD3 webpage](#) | [Snom Service Hub](#) | [Type approval](#) | [User manual](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.