D7

EOS

SmartDisplay

SmartLabel

Plug & Play

USB port

The extension module for the Snom D7xx Series

The Snom D7 is the perfect extension module for the Snom D7xx series desk phones with USB connection. The expansion module allows users who make a lot of calls greater flexibility and productivity by providing 18 SmartLabel LED keys with features such as line hold, speed dial, extension and presence indication. The Snom D7 with its high-resolution black-and-white display can be easily connected via plug-and-play using a USB cable. Up to three extension modules can be connected in series to expand the range of functions enormously. This provides up to 54 additional function keys.

Product variants

D7 (EoS)[2] | black | PN 00004011

D7 | white | PN 00004382

Basics

- Product information
  - Expansion module D7
  - Operating system: Linux
- Placement
  - indoor, desktop
- Daisy-chain up to 3 modules

Dimensions and weight

- Dimensions (L x W x D, approx.) without footstand
  - 158 mm × 140 mm × 40 mm
- Dimensions (H × W × D, approx.) with footstand
  - 158 mm × 140 mm × 220 mm (high angle 46°)
  - 158 mm × 140 mm × 200 mm (low angle 28°)
- Weight (approx.)
  - 400 g without footstand
  - 520 g with footstand

Display and indicators

- Display
  - TFT liquid crystal display (LCD), graphical, monochrome, backlit
  - Size (diagonal): 4.0" (101 mm)
  - Size (W × H): 92 mm × 42 mm
  - Resolution: 384 × 160 pixel
- Function key status indication: 18 multicolour LEDs

Function keys

- 18 SmartLabel keys (with multicolour LED)

Interfaces and connections

- Power options
  - USB powering: 5 V
  - Power adapter:[1] 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W
- Wired interfaces
  - Daisy chaining | USB powering | USB headsets and other accessories
    - USB 2.0 type A port
    - attached USB 2.0 cable with type A plug
  - Power adapter:[1] coaxial power connector (socket)

User interfaces and setup

- Plug & Play
- Completely configurable via host phone

Environmental conditions

- Operating ambient temperature: 0 °C - +35 °C
- Nonoperating (storage) temperature: -10 °C - +45 °C
- Humidity (non-condensing): 5 % - 95 %

Package contents

- Hardware
  - Expansion module D7
  - Footstand
- Documentation
  - Quick Installation Guide

Snom accessories and compatible devices

- Power adapter[1]
  - EU & UK: Snom 10 W PSU (PN 00004570)
  - Americas: Snom 10 W PSU (PN 00004571)
- USB dongle
  - WLAN: A210 (PN 00004384)
  - DECT: A230 (PN 00004386)
- Wired headset via USB
  - Monaural: A330M (PN 00004597)
  - Binaural: A330D (PN 00004598)

- DECT headset via USB (DECT)
  - A150 (PN 00004388)
- IP desk phone (USB)
  - black D715 (PN 00004039)
  - white D715 (EoS) (PN 00004381)[2]
  - black D717 (PN 00004397)
  - white D717 (PN 00004398)
  - black D735 (PN 00004389)
  - white D735 (PN 00004396)
  - black D785 / D785N (PN 00004349)
  - white D785 / D785N (PN 00004392)

10 W PSU	A210	A230	A330M	A330D	A150	D715	D717	D735	D785 / D785N

[1] When two or three modules are used with one phone, a separate power supply needs to be connected to the second module.

[2] EoS (End of sale)

Series overview

D713	D715	D717	D735	D785 / D785N	D7	D7C

Disclaimer

Further information: Snom D7 webpage | Snom Service Hub | Type approval | Warranty information | Company locations

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.